


Illustrated Index

Transmission Housing





- ① SNAP RING
- ② WASHER
- ③ THRUST NEEDLE BEARING
- ④ MAINSHAFT 4TH GEAR
- ⑤ NEEDLE BEARINGS
- ⑥ MAINSHAFT 4TH GEAR COLLAR
- ⑦ THRUST NEEDLE BEARING
- ⑧ THRUST WASHER
- ⑨ 4TH CLUTCH ASSEMBLY
- ⑩ O-RING Replace.
- ⑪ MAINSHAFT
- ⑫ SEALING RING 37 mm
- ⑬ NEEDLE BEARING
- ⑭ SET RING
- ⑮ REVERSE SHIFT FORK
- ⑯ LOCK WASHER Replace.
- ⑰ COUNTERSHAFT REVERSE GEAR COLLAR
- ⑱ THRUST WASHER
- ⑲ COUNTERSHAFT REVERSE GEAR
- ⑳ NEEDLE BEARING
- ㉑ REVERSE SELECTOR
- ㉒ REVERSE SELECTOR HUB
- ㉓ COUNTERSHAFT 4TH GEAR
- ㉔ NEEDLE BEARING (Separate type)
- ㉕ COTTER RETAINER
- ㉖ COTTERS
- ㉗ COUNTERSHAFT 2ND GEAR SPACER
- ㉘ COUNTERSHAFT 2ND GEAR
- ㉙ THRUST NEEDLE BEARING
- ㉚ COUNTERSHAFT 3RD GEAR
- ㉛ NEEDLE BEARING
- ㉜ THRUST NEEDLE BEARING
- ㉝ COUNTERSHAFT 3RD GEAR COLLAR
- ㉞ 3RD CLUTCH ASSEMBLY
- ㉟ O-RINGS Replace.
- ㊱ COUNTERSHAFT
- ㊲ SPACER 31 mm

- ㊳ 2ND CLUTCH ASSEMBLY
- ㊴ O-RINGS Replace.
- ㊵ THRUST WASHER
- ㊶ THRUST NEEDLE BEARING
- ㊷ SECONDARY SHAFT 2ND GEAR
- ㊸ NEEDLE BEARING
- ㊹ THRUST NEEDLE BEARING
- ㊺ SECONDARY SHAFT
- ㊻ SEALING RINGS 35 mm
- ㊼ DIFFERENTIAL OIL SEAL Replace.
- ㊽ REVERSE IDLER GEAR SHAFT/HOLDER
- ㊾ REVERSE IDLER GEAR SHAFT SPRING
- ㊿ STEEL BALL (7/32) #7
- ① NEEDLE BEARING
- ② TRANSMISSION HOUSING
- ③ REVERSE IDLER GEAR
- ④ CONNECTOR STAY
- ⑤ SEALING WASHER Replace.
- ⑥ THRUST SHIM
- ⑦ BEARING OUTER RACE
- ⑧ SNAP RING
- ⑨ SECONDARY SHAFT BALL BEARING
- ⑩ COUNTERSHAFT BALL BEARING
- ⑪ MAINSHAFT BALL BEARING
- ⑫ GASKET Replace.
- ⑬ DOWEL PIN
- ⑭ DIFFERENTIAL ASSEMBLY
- ⑮ BEARING OUTER RACE
- ⑯ THRUST SHIM
- ⑰ DIFFERENTIAL ATF GUIDE RING
- ⑱ 2ND CLUTCH FEED PIPE
- ⑲ 1ST-HOLD CLUTCH FEED PIPE
- ㉑ 4TH CLUTCH FEED PIPE
- ㉒ 1ST CLUTCH FEED PIPE
- ㉓ 3RD CLUTCH FEED PIPE
- ㉔ TORQUE CONVERTER HOUSING
- ㉕ DRIVESHAFT OIL SEAL Replace.

TORQUE SPECIFICATION

No.	TORQUE VALUE	BOLT SIZE	REMARKS
A	54 N·m (5.5 kgf·m, 40 lbf·ft)	10 x 1.25 mm	OIL PRESSURE CHECK BOLT
B	14 N·m (1.4 kgf·m, 10 lbf·ft)	6 x 1.0 mm	
C	12 N·m (1.2 kgf·m, 8.7 lbf·ft)	6 x 1.0 mm	
D	18 N·m (1.8 kgf·m, 13 lbf·ft)	8 x 1.25 mm	