


# Illustrated Index

## Left Side Cover/Transmission





- |   |                                |    |                                      |
|---|--------------------------------|----|--------------------------------------|
| ① | LEFT SIDE COVER                | ③⑥ | PARKING BRAKE PAWL                   |
| ② | DOWEL PIN                      | ③⑦ | PARKING BRAKE PAWL SPRING            |
| ③ | GASKET Replace.                | ③⑧ | PARKING BRAKE PAWL SHAFT             |
| ④ | SEALING WASHER Replace.        | ③⑨ | LOCK WASHER Replace.                 |
| ⑤ | O-RING Replace.                | ④① | PARKING BRAKE STOPPER Selective part |
| ⑥ | 1ST-HOLD CLUTCH FEED PIPE      | ④② | ROLLER PIN                           |
| ⑦ | O-RING Replace.                | ④③ | PARKING BRAKE LEVER                  |
| ⑧ | FEED PIPE FLANGE               | ④④ | WASHER                               |
| ⑨ | SNAP RING                      | ④⑤ | PARKING BRAKE SPRING                 |
| ⑩ | 1ST CLUTCH FEED PIPE           | ④⑥ | ROLLER                               |
| ⑪ | O-RING Replace.                | ④⑦ | COTTER PIN Replace.                  |
| ⑫ | FEED PIPE FLANGE               | ④⑧ | SEALING WASHER Replace.              |
| ⑬ | SNAP RING                      | ④⑨ | CONICAL SPRING WASHER Replace.       |
| ⑭ | CONICAL SPRING WASHER Replace. | ⑤① | TRANSMISSION HANGER/CONNECTOR STAY   |
| ⑮ | BALL BEARING                   | ⑤② | SEALING WASHER Replace.              |
| ⑯ | 1ST-HOLD CLUTCH ASSEMBLY       | ⑤③ | BREATHER JOINT                       |
| ⑰ | O-RING Replace.                | ⑤④ | BREATHER CAP                         |
| ⑱ | THRUST WASHER                  | ⑤⑤ | TRANSMISSION HANGER                  |
| ⑲ | THRUST NEEDLE BEARING          | ⑤⑥ | COUNTERSHAFT SPEED SENSOR            |
| ⑳ | 1ST-HOLD CLUTCH HUB            | ⑤⑦ | O-RING Replace.                      |
| ㉑ | COUNTERSHAFT 1ST GEAR          | ⑤⑧ | ATF COOLER                           |
| ㉒ | ONE-WAY CLUTCH                 | ⑤⑨ | ATF COOLER FILTER/GASKET Replace.    |
| ㉓ | NEEDLE BEARINGS                | ⑥① | SPEED SENSOR COVER                   |
| ㉔ | COUNTERSHAFT 1ST GEAR COLLAR   | ⑥② | LINEAR SOLENOID SHIM Selective part  |
|   | Selective part                 | ⑥③ | O-RING Replace.                      |
| ㉕ | PARKING GEAR                   | ⑥④ | LINEAR SOLENOID                      |
| ㉖ | CONICAL SPRING WASHER Replace. | ⑥⑤ | CONNECTOR STAY                       |
| ㉗ | 1ST CLUTCH ASSEMBLY            | ⑥⑥ | MAINSHAFT SPEED SENSOR               |
| ㉘ | O-RING Replace.                | ⑥⑦ | O-RING Replace.                      |
| ㉙ | THRUST WASHER                  | ⑥⑧ | ATF DIPSTICK                         |
| ㉚ | THRUST NEEDLE BEARING          | ⑥⑨ | ATF DIPSTICK PIPE                    |
| ㉛ | NEEDLE BEARING                 | ⑦① | O-RING Replace.                      |
| ㉜ | MAINSHAFT 1ST GEAR             |    | RETAINER PLATE                       |
| ㉝ | THRUST WASHER                  |    | BALL BEARING                         |
| ㉞ | MAINSHAFT 1ST GEAR COLLAR      |    | COUNTERSHAFT SPEED SENSOR WASHER     |
| ㉟ | PARKING BRAKE PAWL STOPPER     |    |                                      |

#### TORQUE SPECIFICATION

| No. | TORQUE VALUE                     | BOLT SIZE    | REMARKS   |
|-----|----------------------------------|--------------|---|
| A   | 12 N·m (1.2 kgf·m, 8.7 lbf·ft)   | 6 x 1.0 mm   |   |
| B   | 18 N·m (1.8 kgf·m, 13 lbf·ft)    | 8 x 1.25 mm  |   |
| C   | 137 N·m (14.0 kgf·m, 101 lbf·ft) | 24 x 1.25 mm | OIL PRESSURE CHECK BOLT<br>COUNTERSHAFT LOCKNUT<br>(Left-hand threads) Replace. |
| D   | 137 N·m (14.0 kgf·m, 101 lbf·ft) | 23 x 1.25 mm | MAINSHAFT LOCKNUT Replace.  |
| E   | 137 N·m (14.0 kgf·m, 101 lbf·ft) | 24 x 1.25 mm | SECONDARY SHAFT LOCKNUT<br>Replace.   |
| F   | 14 N·m (1.4 kgf·m, 10 lbf·ft)    | 6 x 1.0 mm   |   |
| G   | 49 N·m (5.0 kgf·m, 36 lbf·ft)    | 18 x 1.5 mm  | DRAIN PLUG  |
| H   | 29 N·m (3.0 kgf·m, 22 lbf·ft)    | 8 x 1.25 mm  |   |
| I   | 12 N·m (1.2 kgf·m, 8.7 lbf·ft)   | 6 x 1.0 mm   |   |
| J   | 29 N·m (3.0 kgf·m, 22 lbf·ft)    | 8 x 1.25 mm  | ATF COOLER BOLT   |
| K   | 12 N·m (1.2 kgf·m, 8.7 lbf·ft)   | 6 x 1.0 mm   |   |
| L   | 9.8 N·m (1.0 kgf·m, 7.2 lbf·ft)  | 6 x 1.0 mm   | LINEAR SOLENOID BOLT  |