

# Door lower Trim

## Replacement


### CAUTION:

- Put on gloves to protect you hands.
- When prying with a flat-tip screwdriver, wrap it with protective tape to prevent damage.


### NOTE:

- Take care not to scratch the door.
- Be careful not to damage the door lower trim.


1. Remove the door panel.
2. Remove the plastic cover as necessary.
3. Remove the special nuts and screws from inside of the door.



4. Apply the protective tape along the edge of the door lower trim to the door.
5. Carefully cut the adhesive tape around the entire door lower trim with a utility knife.



6. Slide the door lower trim rearward, and remove it. The clips will stay in the door.





7. Remove the clips.
8. If necessary, replace any damaged clips.



9. Remove the protective tape from the door, and carefully scrape the adhesive tape from the door and door lower trim with a plastic putty knife.
  10. Clean the bonding surface with a sponge dampened in alcohol.
- NOTE: Make sure the bonding surface is kept free of water, oil and grease.
11. Apply primer (3M N-200, or equivalent) to the door lower trim where new adhesive tape will be applied.
  12. Glue the new adhesive tape (3M 4211, or equivalent) to the door lower trim as shown.


▨ : Adhesive tape locations



13. Set the clips on the door lower trim.

NOTE: Apply liquid thread lock to the front bolt and rear bolt.

14. If the adhesive tape is replaced, fold the adhesive backing of the adhesive tape. Hold the trim up, and fit all the clips into the holes in the door, then push on the trim until the clips snap into place.



15. Carefully pull the adhesive backing away, then press the adhesive tape portions to make the adhesive stick.
16. Install the special nuts and screws.
17. Reinstall all removed parts.